




TECHNICAL SPECIFICATIONS

DRIVER POSITION	Left-hand drive with power assisted steering as standard.
GEARBOX	New Iveco gearbox with 10 forward + 2 reverse speeds (5+1 low range, 5+1 high range) and reinforced final drive with third locking differential .
BRAKES	Servo-assisted hydraulic brakes with brake compensator, dual-circuit pump, rear drums and front discs. Mechanical parking brake on rear axle.
DIMENSIONS	Wheelbase 2370 mm, length 4320 mm.
WHEELS/TYRES	205/75R16C.
BODY	2750 x 1600 x 400 mm with headboard (behind cab). Electro-hydraulic three-way tipping with 2 pistons. Top- and bottom-hinged tailgate.
PAYLOAD	Max 1750 kg, gross vehicle weight rating 3500 kg.
SUSPENSION	Front: MacPherson independent suspension with coil springs and shock-absorbers with top mounting equipped with ball bearing. Rear: with parabolic leaf-springs, double-acting shock absorbers and auxiliary leaf spring.
CHASSIS	Bolted steel chassis comprising 2 ASSOFLEX C-section rails.
POWER TAKE-OFF	Predisposed, variable-speed central coupling (on transfer case).
ELECTRICAL SYSTEM	12V regulation-compliant lighting system, reversing light, fog light, flashing beacon.
SPEED	40 km/h.
CAB	Type-approved for 3 seats , sound-insulated with tempered glass, windscreen wipers, split sliding seats, seat-belts, interior heating, type-approved crush protection roll-bar.
STANDARD EQUIPMENT	Spare wheel, jack with wrench, type-approved tow bar for unbraked trailer weight of 1500 kg, electric windows, stereo radio system, rear light guards, wash/wipe kit, light combination switch, user accessories, use and maintenance manual, colour: red.

MITHOS
"SINGLE WHEEL"



VERSIONS

	PART NUMBER	DESCRIPTION
P1	E06 R00C	PERKINS 804C-33 (97/68/EC Step III A Approved), 4-cylinder, 4-stroke, water-cooled diesel with axial fan. Rated power 64 HP (47 kW) @ 2600 rpm, displacement 3331 cc, peak torque 200 Nm @ 1600 rpm.
I1	E06 R00D	IVECO F32-MNS TURBO (97/68/EC Step III A Approved), 4-cylinder, 4-stroke, water-cooled diesel with axial fan. Rated power 75 HP (55 kW) @ 2500 rpm, displacement 3200 cc, peak torque 281 Nm @ 1250 rpm.

OPTIONAL VARIANTS AND ACCESSORIES

PART NUMBER	DESCRIPTION
E06 R001	LONG WHEELBASE version (wheelbase 2670, length 4620, payload 1700 kg) difference
E06 R002	MAX pick-up body 3050 x 1600 x 400 mm (requires LONG WHEELBASE) difference
E06 R008	Side-mounted PTO with disengagement and hydraulic pump (for tipping body)
E06 R009	Electronic odometer
E06 R011	Disengageable rear PTO unit with drive shaft and manual accelerator
E06 R012	Cataphoretic cab coating
E06 R013	Locking rear differential
E06 R014	215/75 R16C tyres (difference)
E06 R015	Hydraulic braking system for trailer weight of 6000 kg
E06 R016	XL cab, width 170 cm - difference
E06 R020	ZF transmission (difference)
E06 R022	External sun visor on cab
E06 R023	Cab-mounted work-light bar with 2 lights
E06 R024	Rear disc brakes (with ventilated front disc brakes) - difference
E06 R027	Air conditioning
E06 R029	Inverter unit for rear PTO
Colour	Colours other than the standard red to be chosen from the catalogue (difference)
VARIANTS AND ACCESSORIES FOR PICK-UP BODY: SEE SECTION 4	