




TECHNICAL SPECIFICATIONS

DRIVER POSITION	Left-hand drive with power assisted steering as standard.
GEARBOX	New Iveco gearbox with 10 forward + 2 reverse speeds (5+1 low range, 5+1 high range) and reinforced final drive with third locking differential .
BRAKES	Servo-assisted hydraulic brakes with brake compensator, dual-circuit pump, rear drums and front discs. Mechanical parking brake on rear axle.
DIMENSIONS	Wheelbase 2370 mm, length 4320 mm.
WHEELS/TYRES	205/75R16C.
BODY	2750 x 1600 x 400 mm with headboard (behind cab). Electro-hydraulic three-way tipping with 2 pistons. Top- and bottom-hinged tailgate.
PAYLOAD	Max 2100 kg, gross vehicle weight rating 4000 kg.
SUSPENSION	Front: MacPherson independent suspension with coil springs and shock-absorbers with top mounting equipped with ball bearing. Rear: with parabolic leaf-springs, double-acting shock absorbers and auxiliary leaf spring.
CHASSIS	Bolted steel chassis comprising 2 ASSOFLEX C-section rails.
POWER TAKE-OFF	Predisposed, variable-speed central coupling (on transfer case).
ELECTRICAL SYSTEM	12V regulation-compliant lighting system, reversing light, fog light, flashing beacon.
SPEED	40 km/h.
CAB	Type-approved for 3 seats , sound-insulated with tempered glass, windscreen wipers, split sliding seats, seat-belts, interior heating, type-approved crush protection roll-bar.
STANDARD EQUIPMENT	Spare wheel, jack with wrench, type-approved tow bar for unbraked trailer weight of 1500 kg, electric windows, stereo radio system, rear light guards, wash/wipe kit, light combination switch, user accessories, use and maintenance manual, colour: red.

MITHOS
"SINGLE WHEEL"



VERSIONS

	PART NUMBER	DESCRIPTION
LDW	E06 P00A	Lombardini LDW 2204 CHD (97/68/EC Step III A Approved), 4-cylinder, 4-stroke, water-cooled diesel with axial fan. Rated power 50 HP (36.6 kW) @ 3000 rpm, displacement 2199 cc, peak torque 132.5 Nm @ 2000 rpm.
P1	E06 P00C	PERKINS 804C-33 (97/68/EC Step III A Approved), 4-cylinder, 4-stroke, water-cooled diesel with axial fan. Rated power 64 HP (47 kW) @ 2600 rpm, displacement 3331 cc, peak torque 200 Nm @ 1600 rpm.

MITHOS
 "SINGLE WHEEL"

OPTIONAL VARIANTS AND ACCESSORIES

PART NUMBER	DESCRIPTION
E06 P001	LONG WHEELBASE version (wheelbase 2670, length 4620, payload 1700 kg) difference
E06 P002	MAX pick-up body 3050 x 1600 x 400 mm (requires LONG WHEELBASE) difference
E06 P003	EXTRA LONG WHEELBASE version (wheelbase 2900) difference
E06 P004	EXTRA MAX pick-up body 3250 x 1750 x 400 mm (requires EXTRA LONG WHEELBASE) difference
E06 P010	Side-mounted PTO with disengagement and hydraulic pump (for tipping body)
E06 P011	Electronic odometer
E06 P012	Rev counter
E06 P013	Disengageable rear PTO unit with drive shaft and manual accelerator
E06 P014	Cataphoretic cab coating
E06 P015	Locking rear differential
E06 P016	215/75 R16C tyres (difference)
E06 P017	XL cab, width 170 cm - difference
E06 P021	ZF transmission (difference)
E06 P023	External sun visor on cab
E06 P024	Cab-mounted work-light bar with 2 lights
E06 P025	Rear disc brakes (with ventilated front disc brakes) - difference
E06 P028	Air conditioning
E06 P029	Inverter unit for rear PTO
Colour	Colours other than the standard red to be chosen from the catalogue (difference)
VARIANTS AND ACCESSORIES FOR PICK-UP BODY: SEE SECTION 4	